Dosatrons

Water-Powered Proportional Dosing Injectors



D3GL Greenline		
△ L/hr	10 - 3,000 L/hr	
Dose Rate	0.2% (1:500) - 2% (1:50)	
⊘ Pressure	0.3 - 6Bar	
Connections	3/4" BSP Thread	



D45RE1.5		
↓ L/hr	100 - 4,500 L/hr	
Dose Rate	0.2% (1:500) - 1.5% (1:67)	
⊘ Pressure	0.5 - 5Bar	
Connections	1 1/4" BSP Thread	



D8RE2		
│ L/hr	500 - 8,000 L/hr	
Dose Rate	0.2% (1:500) - 2% (1:50)	
⊘ Pressure	0.15 - 8Bar	
Connections	1 1/2" M BSP Thread	



D20S		
│ L/hr	1,000 - 20,000 L/hr	
Dose Rate	0.2% (1:500) - 2% (1:50)	
⊘ Pressure	0.2 - 10Bar	
Connections	Ø 63mm PE Compression (grip rings required for PVC)	
	2"M BSP Thread (optional adaptor)	



D30	
↓ L/hr	10,000 - 30,000 L/hr
Dose Rate	0.25% (1:400) - 1.25% (1:80)
⊘ Pressure	0.5 - 8Bar
Connections	2" M / 2"F BSP Thread



Water-Powered Proportional Dosing Injectors



D3GL1 EC		
십 L/hr	8,000 - 30,000 L/hr	
Dose Rate	0.1% (1:1000) - 1% (1:100)	
⊘ Pressure	0.5 - 6Bar	
Connections	3" M BSP Thread	
	DN80 ISO Flanges (Optional)	

D30GL1 EC designed to incorporate an EC sensor, providing a read out of the outgoing EC from the dosing injector.

Dosatron Accessories



PVDF Housing available on certain models



External Injection

Available on certain models.

Allows for the injection of certain corrosive concentrates.



Portable Trolley Packages:
Powdered Coated Black
Trolley c/w 25Ltr barrel.
Recommended for units up
to D45 range (exc. D45RE8)

Seal Kits:

A full range of seal kits to suit application requirements (model dependant)

- AF: Recommended for Alkaline concentrates
- VF: Recommended for Acid concentrates
- V: Recommended for Viscous concentrates

Spares:

A full range of spares available for ALL models, inc. Seal Kits which are recommended to be replaced at least once a year.