



PCJ DRIPPER

COMPACT ON-LINE PRESSURE-COMPENSATING,
CONTINUOUSLY SELF-CLEANING DRIPPER



APPLICATIONS

- Greenhouses, nurseries, citrus.
- Orchards, deciduous and tree irrigation.

SPECIFICATIONS

- Recommended filtration: 130 micron / 120 mesh.
Filtration method is to be selected based on the kind and concentration of the dirt particles existing in the water. Wherever sand exceeding 2 ppm exists in the water, a Hydro-cyclone filter is to be installed before the main filter. When sand/silt/clay solids exceed 100 ppm, pre treatment will be applied according to Netafim™ expert team's instructions.
- TurboNet™ labyrinth with large water passage.
- To be "inserted" into thick-walled pipes (0.9, 1.0, 1.2 mm).
- Injected dripper, very low CV.
- 3 different outlets: nipple, barb to 3 mm ID and barb to 4 mm ID micro-tube.
- UV resistant. Resistant to standard nutrients used in agricultural.
- PCJ on-line drippers meet ISO 9261 Standards with production certified by the Israel Standards Institute (SII).

FEATURES AND BENEFITS

- Pressure compensated: Precise and equal amounts of water are delivered over a broad pressure range. 100% uniformity of water and nutrient distribution along the laterals.
- PCJ-LCNL & PCJ-HCNL with Anti-drain (LCNL & HCNL): Eliminates drainage and refill effect, and improves efficiency in pulse irrigation.
- Continuously self flushing: Flushes debris as it is detected, throughout operation, not just at the beginning or end of a cycle, ensuring uninterrupted dripper operation.
- TurboNet™ labyrinth assures wide water passages, large deep and wide cross section improves clogging resistance. Widest water passages within the dripper.
- Dripper can be positioned exactly where required.
- Number of drippers can be increased so as to increase water quantity supply aimed at meeting tree growth rate requirement.
- Allows the installation of "spider assembly", splitting the drip supply into a number of drip outlets.

DRIPPERS TECHNICAL DATA

PCJ drippers

FLOW RATE* (L/H)	WORKING PRESSURE RANGE (BAR)	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM)	FILTRATION AREA (MM ²)	CONSTANT K	EXPONENT* X	BASE CODE COLOR	CAP COLOR CODE
0.5	0.5 – 4.0	0.54 x 0.60 x 40	1.8	0.5	0	Mustard	Black
1.2	0.5 – 4.0	0.67 x 0.77 x 35	2.0	1.2	0	Brown	Black
2.0	0.5 – 4.0	1.03 x 0.75 x 35	2.0	2.0	0	Red	Black
3.0	0.5 – 4.0	1.03 x 1.08 x 35	2.0	3.0	0	Blue	Black
4.0	0.5 – 4.0	1.32 x 0.95 x 35	2.0	4.0	0	Gray	Black
8.0	0.5 – 4.0	1.60 x 1.05 x 35	2.0	8.0	0	Green	Black
12.0	0.5 – 4.0	1.60 x 1.05 x 17.5	2.0	12.0	0	Fuchsia	Black

*Within working pressure range

PCJ-LCNL drippers

FLOW RATE* (L/H)	WORKING PRESSURE RANGE (BAR)	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM)	FILTRATION AREA (MM ²)	CONSTANT K	EXPONENT* X	SHUT OFF PRESSURE (BAR)	BASE CODE COLOR**	CAP COLOR CODE
0.5	0.7 – 4.0	0.54 x 0.60 x 40	1.8	0.5	0	0.12	Mustard	Black
1.2	0.7 – 4.0	0.67 x 0.77 x 35	2.0	1.2	0	0.12	Brown	Black
2.0	0.7 – 4.0	1.03 x 0.75 x 35	2.0	2.0	0	0.12	Red	Black
3.0	0.7 – 4.0	1.03 x 1.08 x 35	2.0	3.0	0	0.12	Blue	Black
4.0	0.7 – 4.0	1.32 x 0.95 x 35	2.0	4.0	0	0.12	Gray	Black
8.0	0.7 – 4.0	1.60 x 1.05 x 35	2.0	8.0	0	0.12	Green	Black
12.0	0.7 – 4.0	1.60 x 1.05 x 17.5	2.0	12.0	0	0.12	Fuchsia	Black

*Within working pressure range **In addition , PCJ-LCNL is distinguished by the rings around the barb water inlet connector

PCJ-HCNL drippers

FLOW RATE* (L/H)	WORKING PRESSURE RANGE (BAR)	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM)	FILTRATION AREA (MM ²)	CONSTANT K	EXPONENT* X	SHUT OFF PRESSURE (BAR)	BASE CODE COLOR	CAP COLOR CODE
0.5	1.5 – 4.0	0.54 x 0.60 x 40	1.8	0.5	0	0.18	Light Yellow	Black
1.2	1.5 – 4.0	0.67 x 0.77 x 35	2.0	1.2	0	0.18	Light Brown	Black
2.0	1.5 – 4.0	1.03 x 0.75 x 35	2.0	2.0	0	0.18	Pink	Black
3.0	1.5 – 4.0	1.03 x 1.08 x 35	2.0	3.0	0	0.18	Light Blue	Black
4.0	1.5 – 4.0	1.32 x 0.95 x 35	2.0	4.0	0	0.18	Light Gray	Black

* Within working pressure range

DRIPPERS PACKAGE DATA

MODEL	QUANTITY P/BOX (UNITS)	BOX DIMENTIONS (CM X CM X CM)	BOX WEIGHT (KG) AVERAGE
PCJ drippers all the models	13000	57 x 28 x 27	14.3